




ARMSTRONG BIOGUARD ACOUSTIC OP RH100

- Specially developed for high humidity environments
- Anti-microbial performance provides protection against bio-contamination
- Clean Room performance
- Durable, Washable, Smooth surface with 100% sealed edges.
- High sound absorption (NRC 0.90) for reduced reverberation and quieter spaces
- High light reflective finish – 88%
- Humiguard Max® (RH100) Performance



ARMSTRONG BIOGUARD ACOUSTIC OP RH100

Panel Options	Board	Tegular 24/90	Tegular 15/90
 Edge details	 24mm Tee Grid	 24mm Tee Grid	 15mm Tee Grid
 Thickness (mm)	19mm	19mm	19mm
 Dimensions (mm)	600 x 600	1610H	1614H
	1200 x 600	1611H	1615H
 System	24mm exposed grid systems fully demountable	24mm exposed grid systems fully demountable	15mm exposed grid systems fully demountable
 Weight	5.2 kg/m ²		
 Colour	Global White		
 Sound absorption	NRC 0.90		
 Sound attenuation	≤ 29 dB		
 Fire reaction	CLASS 0/1 based on BS 476 Part 6 & 7		
 Light reflectance	≤ 88%		
 Thermal conductivity	$\lambda = 0.060 \text{ W/mk}$		
 Humidity resistance	RH100		
 Clean room	ISO 3 as per ISO 14644-1		
Durability			
Cleanability			
 Sustainability	 EN ISO 14021 32%	Knauf Armstrong provides the widest range of products that have been third party tested and certified by industry leading Eco-classification	

Contact

For further details, please contact your local representative or email asia.support@knaufarmstrong.com