

SELLING POINTS

- Recyclable
- Simple installation, fast construction, saving installation cost and time
- High-end SKU with environmental protection performance, free of benzene, o-benzene plasticizer and other harmful substances, low TVOC
- Applicable to various segments, such as education, retail, office, home and other indoor space

TECHNICAL DATA

Requirement	Standard	Unit	Results
Type of Flooring			Luxury Vinyl Tile with Locking system
Pattern			Wood
Fire test	EN 13501	class	B1
Product Behaviour			
Tile dimensions		mm×mm	230*1220
Total thickness		mm	5.0
wear layer thickness		mm	0.55
Wear layer resistance	EN 660-2	group	T
Slip resistance	DIN 51130		R9
Dimension stability	EN 434	%	Pass
Heat warping degree	EN 434	mm	Pass

ArmstrongFlooring™

Walk On. Walk Strong.

MOLONDIN®

Luxury Vinyl Tile with Locking system

www.armstrongflooring.com

G-SF-VEYTAUX-0620-PRC Printed in China

ArmstrongFlooring™

MOLONDIN®



ArmstrongFlooring™

MOLONDIN®

LVT

WOOD 木纹



LW195



LW195

MOROCCAN SAND



LW194

BALTIC



LW198

MARITIME



LW196

MALIBU SAND

MOLONDIN®
Luxury Vinyl Tile
with Locking system



LW193



LW193

SNOWING



LW189

PENCIL WOOD



LW200

CRAFTED



LW191

PAPRIKA